



- Compact, easy to handle, performance-oriented.
- Ergonomically designed, comfortable, silent.
- Optimum operating and driving speeds.Amount of water on ground can be selected.
- Selectable brush pressure and separate detergent dispensing on request.
- Brushes and squeegees lift automatically.
- Excellent drying action on all floor surfaces.
- High water and power autonomy.
- Recycle tank. Can be fully sanitized.
- Simple, effective maintenance.



CHARACTERISTICS			
Model		RS 61	RS 71
Working width	mm	610	710
Floor scrubber width	mm	840	840
Theoretic operating capacity	m²/h	3700	4300
Power supply		Battery	Battery
Total power	W	1950	1950
Drive		Electric	Electric
BRUSHES			
Diameter/Quantity	mm/n.	310/2	360/2
Motor: Quantity/Power	n./W	2 / 400	2 / 400
Brush rpm	rpm	190	190
Load on brushes	kg	35 - 50	37 - 52
DRIVE TRAIN			
Motor	W	600	600
Maximum speed	km/h	6	6
Climable gradient	%	15	15
SUCTION			
Motor: Quantity/Power	n./W	1/550	1/550
Air flow rate	l/sec	30	30
Aspiration vacuum	kPa	18	18
TANKS			
Tank capacities (Clean/Dirty)	I	90/100	90/100
BATTERIES			
Capacity	V/Ah (C5)	24/265-24/320	24/265-24/320
Operating capacity	h	3-4	3-4
DIMENSIONS			
Length/Width/Height	cm	149x670x128	149x670x128
(without floor scrubber)	cm	14900/00120	149X0/UX120
WEIGHTS			
Without batteries	kg	220	220
265 Ah batteries (C5) (lead/acid)	kg	188	188
320 Ah batteries (C5) (lead/acid)	kg	193	193
NOISE LEVEL			
Noise level	dB(A)	68	68





DEALER