








EVERYTHING IN FULL VIEW





RAPID MAINTENANCE







| CHARACTERISTICS | | |
|-------------------------------|--------|-----------------|
| Model | | Run20 |
| Working width | mm | 960 |
| Floor scrubber width | mm | 1170 |
| Theoretic operating capacity | m²/h | 6700 |
| Power supply | V | 24 |
| Total power | W | 2840 |
| Drive | | Electric |
| BRUSHES | | |
| Diameter/Quantity | mm/n. | 485/2 |
| Motor: Quantity/Power | n./W | 2/400 |
| Brush rpm | rpm | 180 |
| Load on brushes | Kg | 55-100 |
| DRIVE TRAIN | | |
| Motor | W | 1000 |
| Maximum speed | km/h | 7 |
| Climable gradient | % | 15-18* |
| SUCTION | | |
| Motor: Quantity/Power | n./W | 2/500 |
| Air flow rate | l/sec | 45 |
| Aspiration vacuum | mm H2O | 2050 |
| FLOW RATE OF FLUIDS | | |
| water flow | l/min | 1,2 / 2,4 / 3,8 |
| detergent flow rate | % | 0,6 / 1,5 / 3,0 |
| TANKS | | |
| Type | | Triple tank |
| Tank capacities (Clean/Dirty) | 1 | 145/165/5 |
| BATTERIES | | |
| Capacity | V/Ah | 24 / 420 |
| Operating capacity | h | 4 |
| DIMENSIONS | | |
| | | |
| Length/Width/Height | mm | 1810x1015x1490 |
| u-turn corridor | mm | 2900 |
| WEIGHTS | kg | |
| Without batteries | J | 360 |
| With batteries | | 700 |
| Batteries | | 340 |
| NOISE LEVEL | | |
| Noise level | dB(A) | 68 |
| Noise level soft modality | dB(A) | 62 |
| · | , | |



DEALER